







Table S-330-1. Materials: 300 lb Screwed 1/2" - 2"										
Connection Size	Pody	Screen Retainer	Gasket	Bolting	Standard Screen					
in	Body									
1/2", 3/4", 1", 1 1/4", 1 1/2", 2"	ASTM B62	Brass	Copper	N/A	Brass 0,045" perforated †					

 $\ensuremath{ \uparrow}$ Note: Other screen materials available. See page S-321.

Connection Ordering	Ordering	le, Weight dard	Dimensions			Maximum Pressure		Coroor	
Size	ze Code, Standard		A mm	B	C in	Saturated Steam bar	66°C non-shock bar	Screen Retainer Type	Connections
in									
1/2"	F4SC	0,68	89	64	3/8"	21	34	Threaded	ANSI B1.20.1 Screwed
3/4"		0,91	102	73	1/2"				
1"		1,60	121	84					
1 1/4"		2,30	133	102					
1 1/2"		3,40	152	111					
2"	F4SC	5,40	178	140	1/2"	21	34	Threaded	

Shade indicates products that are CE Marked according to the PED (97/23/EC). All the other sizes comply with the Article 3.3 of the same directive.

All dimensions and weights are approximate. Use certified print for exact dimensions. Design and materials are subject to change without notice.